GENPOWER®

GENERATOR

GNP Series



www.genpower.gen.tr

315 SERIES

SYNCHRONOUS ALTERNATORS

4 POLE 50/60 HZ – THREE PHASE

Your Power is the Core Our Business. . .





STANDARD SPECIFICATIONS

TECHNICAL SPECIFICATIONS

GENERAL SPECIFICATIONS

GENPOWER, is an independent and internationally recognized power producer, specializing exclusively on manufacturing of synchronous alternators.

Genpower focuses its corporate mission on original and self-made designs; innovative solutions and provide long-term and sustainable development.

Turkish and foreign technical teams are always working with their knowhow and experience in order to meet universal demands and projects and to have a continuous increase in the performance, total lifespan and overall reliability of the products. Genpower continues the R&D studies with universities both in Turkey and in other countries who have comprehensive knowledge on its products.

Genpower synchronous alternators are proven to endure the harshest environmental applications. They proved to be one of the most reliable and preferred alternator brands all over the world with their brushless and self-exciting system, electronic voltage regulator (AVR), stable wave form, low harmonic distortion and high efficiency.

In case of a demand, Genpower can also produce direct current (DC) alternators, 50-60 Hz low voltage (LV) alternators, medium voltage alternators, high voltage alternators; alternators for light towers, welding alternators, IP44 and PI54 class alternators for marine applications, variable speed alternators for telecom projects and cranes; high frequency alternators for ground power units, radars, planes and helicopters.

PRODUCT APPLICATION

Genpower alternators are mainly used in the application of diesel, gasoline and gas generator groups. They are also able to operate with steam or hydraulic turbines. They operate in all configurations of emergency generator groups, power plants or continuous power sources.

- Industrial and commercial complex.
- Telecommunication and cell-phone towers, radio and television transmitters
- Defense industry and military projects.
- Construction sites, mining, stone crushers and mixing plants, light towers
- Agriculture and irrigation; cattle and chicken farms
- Hotels and hospitals, lofts, care centers, clinics
- Offices, shops, factories, workshops, buildings, sports complexes, stores, malls, banks, gas stations
- Rental companies, mobile service vehicles, mobile hospitals, and other mobile facilities
- Airports, initial starting of the air vehicles, ground services

STANDARDS

Genpower synchronous alternators are designed and manufactured in compliance with TSE 60034-1; IEC 60034-22; GB755; BS4999-5000; NEMA MG 1.22 CE marking approved and are also accredited with ISO 9001: 2008 and ISO 14001:2004.

GENPOWER GENERATOR

GENPOWER reserves the right to change the values and pictures in this catalogue at any time without notice due to the ongoing developments in generator technology.

CONSTRUCTION

Genpower alternators are made according to the requirements of the standard TSE 60034-1; IEC 60034-1.Using the best quality standards during manufacturing, the result is safe operation and great durability. Mounting styles normally supplied are; Single bearing with coupling by means of flanges and flexible disc. Double bearing with coupling by means of flange.

WINDING & ELECTRICAL PERFORMANCE


All alternators stators windings are 2/3 pitch. This eliminates triple (3rd, 9th, 15th …) harmonics on the voltage waveform and is found to be the optimum design for trouble-free supply of non-linear loads. The 2/3 pitch design avoids excessive neutral currents sometimes seen with higher winding pitches, when in parallel with the mains. A fully connected damper winding reduces oscillations during paralleling. This winding, with the 2/3 pitch and carefully selected pole and tooth designs, ensures very low waveform distortion.

High quality siliceous metals are used in the body and it increases the efficiency of the alternator.

EXCITATION SYSTEM & AUTOMATIC VOLTAGE REGULATORS (AVR)

The self-warning control system supplies power from the main stator to the warning stator via AVR. The high efficiency semiconductors of AVR (diodes transmitters, etc.) allow the low permanent voltage to be positively raised. Three-phase excitation rotor diode bridge output supplies the main rotor excitation area. There is a varistor that protects the diode bridge and acts as a plug from shocks that may be short-circuited or similar.
With the Frequency / Voltage ratio (U / F) system, it protects AVR and alternator against low frequency. It provides voltage adjustment opportunity within ± 5% limits for external voltage adjustment.
Automatic Voltage Regulators (AVR) are specially designed and catered for both single and parallel running operations for both self-excited and separately excited system (PMG).





GENPOWER reserves the right to change the values and pictures in this catalogue at any time without notice due to the ongoing developments in generator technology.

TERMINAL & TERMINAL BOX

Standard generators are 3-phase reconnect able with 12 ends brought out to the terminals, which are mounted on a cover at the non-drive end of the generator. A sheet steel terminal box contains the AVR and provides ample space for the customers' wiring and gland arrangements. It has removable panels for easy access.

INSULATION / IMPREGNATION (VPI)

The insulation system is class H. All winding components are impregnated in an unsaturated polyester resin of 200 class temperature. The impregnation provides much needed rigidity and protection against the harsh environment, typical for the generators applications.

Genpower alternators are delivered with Genpower insulation system. This insulation system is based on the “Vacuum Pressure Impregnation” (VPI) system which was developed in cooperation with the most renowned suppliers of insulation material all over the world. Using special epoxy based resin; this insulation system ensures perfect winding insulation of the alternators and does not emit harmful gases into the environment.

DYNAMIC BALANCING

The rotating (Main rotor, exciter rotor, diode group, fan) parts are dynamically balanced with greater precision than that required by the Standard TSE EN IEC 60034-14 and ISO2372, ensuring minimum levels of residual unbalance.

WAVEFORMS / RADIO INTERFERENCE

The alternators are designed to give an excellent output waveform. The total harmonic content of line voltage waveform on no load is less than 5% as per limits specified by TSE / IEC Standards.

The Alternators are having negligible Radio Frequency Interference and meets the general limits permitted by VDE 0875 (N). TIF value is <50 and THF value is
<2%.

TRANSIENT RATINGS

Transient voltage drop due to application of full load at 0.8 power factor is less than 18% output voltage recovers to within 3% of the rated value in less than 0.3 seconds.

CONTINUOUS DUTY / S1 – AMBIENT TEMPERATURE / 40ºC

The alternator operates at rated power for an unlimited time with the possibility of overload up to 10% for 1 hour every 12 hours, without damage to its insulation system. The S1, also called continuous or prime duty is applied mainly where there is not another power source available, such as; groups for rental groups for irrigation, refrigeration and application for peak hours. For continuous duty, it is accepted a temperature raise in the windings of up to 125ºC.

STANDBY DUTY – AMBIENT TEMPERATURE / 40ºC

The generator group operates as energy backup with variable loads in emergency situations in places supplied by the grid / utility company or another main power source. In this kind of duty, the machine does not accept overloads and operates with variable loads up to the rated power of the stand-by duty (40ºC). A raise in the winding temperature of up to 150ºC is accepted (as per Standard of TSE 60034 / IEC 60034), However if that happens the useful life of the alternator reduces 2 to 6 times. The use of the alternator in stand-by duty is limited to 500 hours a year.

OPERATING CONDITIONS

When choosing an alternator, “ALTITUDE”, “AMBIENT TEMPERATURE” and “POWER FACTOR” should be taken into consideration. Power drops should be calculated with the help of the table below and power determination should be done accordingly.

GENPOWER reserves the right to change the values and pictures in this catalogue at any time without notice due to the ongoing developments in generator technology.

ALTIDUDE

The rated power refers to installations up to 1000 meter above sea level. For applications over this altitude, the following power correction factor must be applied.

Altitude (m)	<1000	<1500	<2000	<2500	<3000
K Factor	1	96	0.93	0.90	0.86

AMBIENT TEMPERATURE

The rated powers refer to installation with ambient temperature of 40ºC. For applications different from 40ºC, the following power correction factor must be applied.

Ambient Temperature	30 ºC	35 ºC	40 ºC	45 ºC	50 ºC	55 ºC
K Factor	1.04	1.02	1	0.96	0.93	0.90

POWER FACTOR (COS Q)

The nominal power factor is 0.8 lagging. For application with power factor value different from 0.8, the following correction factor must be applied.

Power Factor (Cos Q)	0.80	0.70	0.60	0.30	0
K Factor	1	0.93	0.88	0.82	0.80

THERMAL INSULATION CLASS

Insulation class governs the maximum permissible temperature an alternator can operate without damaging the insulation system.

Insulation Class	Maximum Permissible Temperature
F	155 ºC
H	180 ºC

TEMPERATURE RISE

Temperature rise is the increase in temperature above ambient temperature 40ºC ratings.

Temperature Rise	Temperature ºC	*Stand-by application allows windings to run hotter than the class H temperature rise limit, therefore for an ambient of;*
B	80 ºC	
F	105 ºC	**40º Temperature Rise: 150ºC**
H	125 ºC	**27ºC Temperature Rise: 163ºC**

GENERATOR SET RATINGS

The tables below summarize the definitions accordance to TSE 8528-1 / ISO 8528-1 for the generator set and a combination of TSE 8528-3 / ISO 8528-3 and TSE 60034-1 / IEC 60034-1 for the alternator.

Genset Rating	Emergency Standby Power(ESP)	Limited Time Prime Power(LTP)	Prime Rated Power (PRP)	Continuous Operating Power(COP)
Load Type	Variable	Constant	Variable	Constant
Annual Operating Hors	200	500	Unlimited	Unlimited
Average Load	70%	100%	70%	100%
Overload	No	No	10% 1 Hour in Every 12	No
Alternator Rating	Standby	Standby	Continuous	Continuous
Duty Cycle	S10	S10	S1	S1
Alternator Ratings	Standby 150/40°C	Standby 150/40°C	Class H 125/40°	Class H 125/40°
	Standby 163/27°C	Standby 163/27°C	Class H 105/40°	Class H 105/40°

GENPOWER reserves the right to change the values and pictures in this catalogue at any time without notice due to the ongoing developments in generator technology.

400 V - 50 HZ

STANDARD SPECIFICATIONS

TECHNICAL SPECIFICATIONS

ALTERNATOR TECHNICAL DATA – 50HZ

4 POLE 1500 RPM 50 HZ

TYPICAL DATA

Insulation class	H	**Control system**	Self Excited
Winding pitch	2/3- (N ° 6)	**A.V.R. model**	Standard SX440
Wires	12	**Voltage regulation**	± 1.0 %
Drip proof	IP 23	**Sustained short-circuit current**	300% (3 IN) : 10s
Altitude	≤ 1000 m	**Total harmonic (*) TGH / THC**	< 4 %
Overspeed	2250 min-1	**Wave form: NEMA = TIF - (*)**	< 50
Air flow	0,8 m³/sec.	**Wave form: I.E.C. = THF - (*)**	< 2 %
Bearing drive	-	**Bearing non-drive**	6314 – 2RZ

(*)Total harmonic content line to line, at no load or full rated linear and balanced load

50 Hz kVA / kW – Power Factor (CosQ) = 0,8

Duty Ambient C°		**Continuous / 40 ° C**			**Standby / 27 °C**		
Class / C° rise		H / 125 ° K			H / 163° K		
Series Star(V)		380/220	400/231	415/240	380/220	400/231	415/240
Parallel Star (V)		190/110	200/115	208/120	190/110	200/115	208/120
Series Delta(V)		220	230	240	220	230	240
GNP 315 S	kVA	373	373	380	410	410	418
	kW	298	298	304	328	328	334
GNP 315 M	kVA	409	409	417	450	450	459
	kW	327	327	334	360	360	367
GNP 315 MX	kVA	432	432	441	475	475	485
	kW	346	346	353	380	380	388
GNP 315 MXA	kVA	468	468	477	515	515	525
	kW	374	374	382	412	412	420
GNP 315 L	kVA	514	514	524	565	565	576
	kW	411	411	419	452	452	461

REACTANCES (%) – TIME CONSTANTS (ms) : CLASS: H / 400 V

VOLTAGE SERIAL STAR	400 V	315 S	315 M	315 MX	315 MXA	315 L
DIR. AXIS SYNCHRONOUS	Xd	2,85	2,71	2,45	2,11	2,01
DIR. AXIS TRANSIENT	X'd	0,18	0,18	0,16	0,19	0,175
DIR. AXIS SUBTRANSIENT	X''d	0,13	0,13	0,12	0,13	0,12
QUAD.AXIS REACTANCE	Xq	2,4	2,33	2,15	1,38	1,23
QUAD. AXIS SUBTRANSIENT	X''q	0,36	0,32	0,28	0,16	0,14
LEAKAGE REACTANCE	XL	0,06	0,06	0,05	0,08	0,08
NEGATIVE SEQUENCE	X2	0,24	0,22	0,21	0,14	0,12
ZERO SEQUENCE	X0	0,09	0,09	0,085	0,09	0,08

OTHER DATA – CLASS H / 400 V


T'd TRANSIENT TIME CONST.	0,08 s	0,08 s	0,08 s	0,08 s	0,08 s
T''d SUB-TRANSTIME CONST.	0,019 s	0,019 s	0,019 s	0,019 s	0,019 s
T'do O.C. FIELD TIME CONST.	1,7 s	1,7 s	1,7 s	1,7 s	1,7 s
Ta ARMATURE TIME CONST.	0,018 s	0,018 s	0,018 s	0,018 s	0,018 s
SHORT CIRCUIT RATIO	1/Xd	1/Xd	1/Xd	1/Xd	1/Xd


GENPOWER reserves the right to change the values and pictures in this catalogue at any time without notice due to the ongoing developments in generator technology.


3 PHASE / 400V / 50 HZ EFFICIENCY CURVES & PERCENT TRANSIENT VOLTAGE DIP & ALTERNATOR WINDINGS


400 V - 50 HZ

STANDARD SPECIFICATIONS

















ALTERNATOR WINDINGS

4 Pole	50 Hz - 1500 R.P.M						
Phase	3	3	3	3	3	1	1
Connections							
Number of Leads	6	6	12	12	12	12	12
Standard Winding	380 - 400 - 415V	220 - 240V	380 - 400 - 415V	220 - 240V	190 - 208V	220 - 240V	220 - 240V

TECHNICAL SPECIFICATIONS

High quality 100% copper wires are used in the rotors, stators and excitation wirings of GENPOWER alternators. All metal sheets used in the production are siliceous metals. Therefore, GNP alternators have higher efficiency compared to exemplary products.

GENPOWER GENERATOR

GENPOWER reserves the right to change the values and pictures in this catalogue at any time without notice due to the ongoing developments in generator technology.

480 V - 60 HZ

STANDARD SPECIFICATIONS

ALTERNATOR TECHNICAL DATA – 60HZ

4 POLE 1800 RPM 60 HZ

TYPICAL DATA

Insulation class	H	**Control system**	Self Excited
Winding pitch	2/3- (N ° 6)	**A.V.R. model**	Standard SX440
Wires	12	**Voltage regulation**	± 1.0 %
Drip proof	IP 23	**Sustained short-circuit current**	300% (3 IN) : 10s
Altitude	≤ 1000 m	**Total harmonic (*) TGH / THC**	< 4 %
Overspeed	2250 min-1	**Wave form: NEMA = TIF - (*)**	< 50
Air flow	0.99 m³/sec.	**Wave form: I.E.C. = THF - (*)**	< 2 %
Bearing drive	-	**Bearing non-drive**	6314 – 2RZ

(*)Total harmonic content line to line, at no load or full rated linear and balanced load

60 HZ – kVA / kW – Power Factor (Cos Q) = 0,8

Duty Ambient C°		**Continuous / 40 ° C**			**Standby / 27 °C**		
Class / C° rise		H / 125 ° K			H / 163° K		
Series Star(V)		416/240	440/254	480/277	416/240	440/254	480/277
Parallel Star (V)		208/120	220/127	240/138	208/120	220/120	240/138
Series Delta(V)		240	254	277	240	254	277
GNP 315 S	kVA	421	443	466	463	487	513
	kW	336	354	373	370	390	410
GNP 315 M	kVA	476	501	527	524	551	580
	kW	381	401	422	419	441	464
GNP 315 MX	kVA	490	516	543	539	568	597
	kW	392	413	434	431	454	478
GNP 315 MXA	kVA	528	556	585	581	612	644
	kW	422	445	468	465	490	515
GNP 315 L	kVA	580	611	643	638	672	707
	kW	464	489	514	510	538	566

TECHNICAL SPECIFICATIONS

REACTANCES (%) – TIME CONSTANTS (ms) : CLASS: H / 480 V

VOLTAGE SERIAL STAR	480 V	315 S	315 M	315 MX	315 MXA	315 L
DIR. AXIS SYNCHRONOUS	Xd	2,9925	2,8455	2,5725	2,5305	2,52
DIR. AXIS TRANSIENT	X'd	0,189	0,189	0,168	0,1617	0,1596
DIR. AXIS SUB□RANSIENT	X''d	0,1365	0,1365	0,126	0,12075	0,1155
QUAD.AXIS REACTANCE	Xq	2,52	2,4465	2,2575	2,226	2,205
QUAD. AXIS SUBTRANSIENT	X''q	0,378	0,336	0,294	0,2835	0,2625
LEAKAGE REACTANCE	XL	0,063	0,063	0,0525	0,0525	0,0525
NEGATIVE SEQUENCE	X2	0,252	0,231	0,2205	0,21	0,21
ZERO SEQUENCE	X0	0,0945	0,0945	0,08925	0,084	0,084

OTHER DATA – CLASS H / 480 V


T'd TRANSIENT TIME CONST.	0,08 s	0,08 s	0,08 s	0,08 s	0,08 s
T''d SUB-TRANSTIME CONST.	0,019 s	0,019 s	0,019 s	0,019 s	0,019 s
T'do O.C. FIELD TIME CONST.	1,7 s	1,7 s	1,7 s	1,7 s	1,7 s
Ta ARMATURE TIME CONST.	0,018 s	0,0018 s	0,018 s	0,018 s	0,018 s
SHORT CIRCUIT RATIO	1/Xd	1/Xd	1/Xd	1/Xd	1/Xd


GENPOWER GENERATOR


GENPOWER reserves the right to change the values and pictures in this catalogue at any time without notice due to the ongoing developments in generator technology.


3 PHASE / 480V / 60 HZ EFFICIENCY CURVES & PERCENT TRANSIENT VOLTAGE DIP & ALTERNATOR WINDINGS


480 V - 60 HZ

















ALTERNATOR WINDINGS

4 Pole	60 Hz - 1800 R.P.M						
Phase	3	3	3	3	3	1	1
Connections							
Number of Leads	6	6	12	12	12	12	12
Standard Winding	380 - 480V	220 - 277V	380 - 480V	220 - 277V	190 - 240V	220 - 240V	220 - 240V

High quality 100% copper wires are used in the rotors, stators and excitation wirings of GENPOWER alternators. All metal sheets used in the production are siliceous metals. Therefore, GNP alternators have higher efficiency compared to exemplary products.

STANDARD SPECIFICATIONS

TECHNICAL SPECIFICATIONS


GENPOWER GENERATOR


GENPOWER reserves the right to change the values and pictures in this catalogue at any time without notice due to the ongoing developments in generator technology.

DIMENSIONS

DIMENSIONS

CONNECTION TYPE		SIZE					COUPLING DISC					
SAE	MODEL	C-G	K	L	M	N	SAE	AN	AR	AS	AT	V
1	315 S	483	1175	1100	584	493	14	25,4	8	13,5	438,1	314,2
	315 M	504	1175	1100	584	493	FLANGE ADAPTER					
	315 MX-MXA	530	1265	1190	674	583	SAE	R	S	T	W	X
	315 L	530	1265	1190	674	583	1	12	12,7	530,2	511,1	553





SPECIAL PRODUCTS / NON - STANDARDIZED

Light Tower Alternators	Direct Current Alternators - (DC)
Welding Alternators	Medium Voltage Alternators - (MV)
High Frequency Alternators	High Voltage Alternators - (HV)
Variable Speed Alternators	IP44 and IP54 Class Alternators - (Marine)

QUALITY DOCUMENTS & CERTIFICATES

Trademark Registration Certificate	Industrial Registry Certificate	TSE – Turkish Standards Institution Certificate
Capacity Report (32400 Units /Year)	Certificate of Manufacturing Competence	Certificate of Competency for After Sales Services
ISO 9001 - 2015 Certificate	TSE- Service Adequacy Certificate	Made in Turkey Certificate- For Generator/ 1 - 5000 kVA
ISO 14001 - 2015 Certificate	TS EN 60034 - 1 Certificate	
OHSAS 18001 - 2007 Certificate		

STANDARD SPECIFICATIONS

TECHNICAL SPECIFICATIONS

GENPOWER GENERATOR

GENPOWER reserves the right to change the values and pictures in this catalogue at any time without notice due to the ongoing developments in generator technology.

GENPOWER®
GENERATOR

Your Power is the Core Our Business...





SCAN ME

www.genpower.gen.tr

ISO 9001:2008
OHSAS 18001:2007
ISO 14001:2004

Central District, Kağıthane Street
Y Office No:5 Interior No:37, 34406
Kağıthane-ISTANBUL / TURKEY
+90 (536) 351 34 00
+90 (536) 351 65 00
+90 (212) 294 94 22
+90 (212) 294 94 33
info@genpower.gen.tr