# GENPOWER®

GENERATOR

# GNP Series



www.genpower.gen.tr

# 355 SERIES

# SYNCHRONOUS ALTERNATORS

## 4 POLE 50/60 HZ – THREE PHASE

*Your Power is the Core Our Business. . .*





### GENERAL SPECIFICATIONS

GENPOWER, is an independent and internationally recognized power producer, specializing exclusively on manufacturing of synchronous alternators.

Genpower focuses its corporate mission on original and self-made designs; innovative solutions and provide long-term and sustainable development.

Turkish and foreign technical teams are always working with their knowhow and experience in order to meet universal demands and projects and to have a continuous increase in the performance, total lifespan and overall reliability of the products. Genpower continues the R&D studies with universities both in Turkey and in other countries who have comprehensive knowledge on its products.

Genpower synchronous alternators are proven to endure the harshest environmental applications. They proved to be one of the most reliable and preferred alternator brands all over the world with their brushless and self-exciting system, electronic voltage regulator (AVR), stable wave form, low harmonic distortion and high efficiency.

In case of a demand, Genpower can also produce direct current (DC) alternators, 50-60 Hz low voltage (LV) alternators, medium voltage alternators, high voltage alternators; alternators for light towers, welding alternators, IP44 and PI54 class alternators for marine applications, variable speed alternators for telecom projects and cranes; high frequency alternators for ground power units, radars, planes and helicopters.

STANDARD SPECIFICATIONS

TECHNICAL SPECIFICATIONS

### PRODUCT APPLICATION

Genpower alternators are mainly used in the application of diesel, gasoline and gas generator groups. They are also able to operate with steam or hydraulic turbines. They operate in all configurations of emergency generator groups, power plants or continuous power sources.

- Industrial and commercial complex.
- Telecommunication and cell-phone towers, radio and television transmitters
- Defense industry and military projects.
- Construction sites, mining, stone crushers and mixing plants, light towers
- Agriculture and irrigation; cattle and chicken farms
- Hotels and hospitals, lofts, care centers, clinics
- Offices, shops, factories, workshops, buildings, sports complexes, stores, malls, banks, gas stations
- Rental companies, mobile service vehicles, mobile hospitals, and other mobile facilities
- Airports, initial starting of the air vehicles, ground services

### STANDARDS

Genpower synchronous alternators are designed and manufactured in compliance with TSE 60034-1; IEC 60034-22; GB755; BS4999-5000; NEMA MG 1.22 CE marking approved and are also accredited with ISO 9001: 2008 and ISO 14001:2004.

GENPOWER GENERATOR

GENPOWER reserves the right to change the values and pictures in this catalogue at any time without notice due to the ongoing developments in generator technology.

STANDARD SPECIFICATIONS

## CONSTRUCTION

Genpower alternators are made according to the requirements of the standard TSE 60034-1; IEC 60034-1.Using the best quality standards during manufacturing, the result is safe operation and great durability. Mounting styles normally supplied are; Single bearing with coupling by means of flanges and flexible disc. Double bearing with coupling by means of flange.

### WINDING & ELECTRICAL PERFORMANCE

All alternators stators windings are 2/3 pitch. This eliminates triple (3rd, 9th, 15th …) harmonics on the voltage waveform and is found to be the optimum design for trouble-free supply of non-linear loads. The 2/3 pitch design avoids excessive neutral currents sometimes seen with higher winding pitches, when in parallel with the mains. A fully connected damper winding reduces oscillations during paralleling. This winding, with the 2/3 pitch and carefully selected pole and tooth designs, ensures very low waveform distortion.

High quality siliceous metals are used in the body and it increases the efficiency of the alternator.

## EXCITATION SYSTEM & AUTOMATIC VOLTAGE REGULATORS (AVR)

The self-warning control system supplies power from the main stator to the warning stator via AVR. The high efficiency semiconductors of AVR (diodes transmitters, etc.) allow the low permanent voltage to be positively raised. Three-phase excitation rotor diode bridge output supplies the main rotor excitation area. There is a varistor that protects the diode bridge and acts as a plug from shocks that may be short-circuited or similar.
With the Frequency / Voltage ratio (U / F) system, it protects AVR and alternator against low frequency. It provides voltage adjustment opportunity within ± 5% limits for external voltage adjustment.
Automatic Voltage Regulators (AVR) are specially designed and catered for both single and parallel running operations for both self-excited and separately excited system (PMG).


TECHNICAL SPECIFICATIONS




SX 440



MX 341 + PMG




REFER TO GENERATOR WIRING DIAGRAM FOR CONNECTION DETAILS

**SUMMARY OF AVR CONTROLS**

| CONTROL | FUNCTION | DIRECTION |
|---|---|---|
| Volts | To adjust generator output voltage | Clockwise increases output voltage |
| Stability | To prevent voltage hunting | Clockwise increase the damping effect |
| Ufro | To set the ufro knee point | Clockwise reduces the knee point frequency |
| Droop | To set the generator droop to 5% at 0pf | Clockwise increases the droop |
| Vtrim | To optimise analogue input sensitivity | Clockwise increases the gain or sensitivity |
| Exc trip | To set the over excitation cut off level | Clockwise increase the cut off level |
| Dip | To set the frequency related voltage dip | Clockwise increases the voltage dip |



GENPOWER reserves the right to change the values and pictures in this catalogue at any time without notice due to the ongoing developments in generator technology.

## TERMINAL & TERMINAL BOX

Standard generators are 3-phase reconnect able with 12 ends brought out to the terminals, which are mounted on a cover at the non-drive end of the generator. A sheet steel terminal box contains the AVR and provides ample space for the customers' wiring and gland arrangements. It has removable panels for easy access.

## INSULATION / IMPREGNATION (VPI)

The insulation system is class H. All winding components are impregnated in an unsaturated polyester resin of 200 class temperature. The impregnation provides much needed rigidity and protection against the harsh environment, typical for the generators applications.

Genpower alternators are delivered with Genpower insulation system. This insulation system is based on the “Vacuum Pressure Impregnation” (VPI) system which was developed in cooperation with the most renowned suppliers of insulation material all over the world. Using special epoxy based resin; this insulation system ensures perfect winding insulation of the alternators and does not emit harmful gases into the environment.

## DYNAMIC BALANCING

The rotating (Main rotor, exciter rotor, diode group, fan) parts are dynamically balanced with greater precision than that required by the Standard TSE EN IEC 60034-14 and ISO2372, ensuring minimum levels of residual unbalance.

## WAVEFORMS / RADIO INTERFERENCE

The alternators are designed to give an excellent output waveform. The total harmonic content of line voltage waveform on no load is less than 5% as per limits specified by TSE / IEC Standards.

The Alternators are having negligible Radio Frequency Interference and meets the general limits permitted by VDE 0875 (N). TIF value is <50 and THF value is
<2%.

## TRANSIENT RATINGS

Transient voltage drop due to application of full load at 0.8 power factor is less than 18% output voltage recovers to within 3% of the rated value in less than 0.3 seconds.

## CONTINUOUS DUTY / S1 – AMBIENT TEMPERATURE / 40ºC

The alternator operates at rated power for an unlimited time with the possibility of overload up to 10% for 1 hour every 12 hours, without damage to its insulation system. The S1, also called continuous or prime duty is applied mainly where there is not another power source available, such as; groups for rental groups for irrigation, refrigeration and application for peak hours. For continuous duty, it is accepted a temperature raise in the windings of up to 125ºC.

## STANDBY DUTY – AMBIENT TEMPERATURE / 40ºC

The generator group operates as energy backup with variable loads in emergency situations in places supplied by the grid / utility company or another main power source. In this kind of duty, the machine does not accept overloads and operates with variable loads up to the rated power of the stand-by duty (40ºC). A raise in the winding temperature of up to 150ºC is accepted (as per Standard of TSE 60034 / IEC 60034), However if that happens the useful life of the alternator reduces 2 to 6 times. The use of the alternator in stand-by duty is limited to 500 hours a year.

## OPERATING CONDITIONS

When choosing an alternator, “ALTITUDE”, “AMBIENT TEMPERATURE” and “POWER FACTOR” should be taken into consideration. Power drops should be calculated with the help of the table below and power determination should be done accordingly.



GENPOWER reserves the right to change the values and pictures in this catalogue at any time without notice due to the ongoing developments in generator technology.

STANDARD SPECIFICATIONS

## ALTIDUDE

The rated power refers to installations up to 1000 meter above sea level. For applications over this altitude, the following power correction factor must be applied.

| Altitude (m) | <1000 | <1500 | <2000 | <2500 | <3000 |
|---|---|---|---|---|---|
| K Factor | 1 | 96 | 0.93 | 0.90 | 0.86 |

## AMBIENT TEMPERATURE

The rated powers refer to installation with ambient temperature of 40ºC. For applications different from 40ºC, the following power correction factor must be applied.

| Ambient Temperature | 30 ºC | 35 ºC | 40 ºC | 45 ºC | 50 ºC | 55 ºC |
|---|---|---|---|---|---|---|
| K Factor | 1.04 | 1.02 | 1 | 0.96 | 0.93 | 0.90 |

## POWER FACTOR ( COS Q)

The nominal power factor is 0.8 lagging. For application with power factor value different from 0.8, the following correction factor must be applied.

| Power Factor (Cos Q) | 0.80 | 0.70 | 0.60 | 0.30 | 0 |
|---|---|---|---|---|---|
| K Factor | 1 | 0.93 | 0.88 | 0.82 | 0.80 |

## THERMAL INSULATION CLASS

Insulation class governs the maximum permissible temperature an alternator can operate without damaging the insulation system.

| Insulation Class | Maximum Permissible Temperature |
|---|---|
| F | 155 ºC |
| H | 180 ºC |

## TEMPERATURE RISE

Temperature rise is the increase in temperature above ambient temperature 40ºC ratings.

| Temperature Rise | Temperature ºC | *Stand-by application allows windings to run hotter than the class H temperature rise limit, therefore for an ambient of;* |
|---|---|---|
| B | 80 ºC | |
| F | 105 ºC | **40º Temperature Rise: 150ºC** |
| H | 125 ºC | **27ºC Temperature Rise: 163ºC** |

TECHNICAL SPECIFICATIONS

## GENERATOR SET RATINGS

The tables below summarize the definitions accordance to TSE 8528-1 / ISO 8528-1 for the generator set and a combination of TSE 8528-3 / ISO 8528-3 and TSE 60034-1 / IEC 60034-1 for the alternator.

| Genset Rating | Emergency Standby Power(ESP) | Limited Time Prime Power(LTP) | Prime Rated Power (PRP) | Continuous Operating Power(COP) |
|---|---|---|---|---|
| Load Type | Variable | Constant | Variable | Constant |
| Annual Operating Hors | 200 | 500 | Unlimited | Unlimited |
| Average Load | 70% | 100% | 70% | 100% |
| Overload | No | No | 10% 1 Hour in Every 12 | No |
| Alternator Rating | Standby | Standby | Continuous | Continuous |
| Duty Cycle | S10 | S10 | S1 | S1 |
| Alternator Ratings | Standby 150/40°C | Standby 150/40°C | Class H 125/40° | Class H 125/40° |
| | Standby 163/27°C | Standby 163/27°C | Class H 105/40° | Class H 105/40° |

GENPOWER reserves the right to change the values and pictures in this catalogue at any time without notice due to the ongoing developments in generator technology.

400 V - 50 HZ

STANDARD SPECIFICATIONS

## ALTERNATOR TECHNICAL DATA – 50HZ

**4 POLE 1500 RPM 50 HZ**

### TYPICAL DATA

| | | | |
|---|---|---|---|
| **Insulation class** | H | **Control system** | Self Excited |
| **Winding pitch** | 2/3- (N ° 6) | **A.V.R. model** | Standard SX440/MX 321+PMG |
| **Wires** | 12 | **Voltage regulation** | ± 1.0 % |
| **Drip proof** | IP 23 | **Sustained short-circuit current** | 300% (3 IN) : 10s |
| **Altitude** | ≤ 1000 m | **Total harmonic (*) TGH / THC** | < 4 % |
| **Overspeed** | 2250 d./dak. | **Wave form: NEMA = TIF - (*)** | < 50 |
| **Air flow** | 1,035 m³/san | **Wave form: I.E.C. = THF - (*)** | < 2 % |
| **Bearing drive** | - | **Bearing non-drive** | 6314 – 2RZ |

(*)Total harmonic content line to line, at no load or full rated linear and balanced load

### 50 Hz kVA / kW – Power Factor (CosQ) = 0,8

| **Duty Ambient C°** | | **Continuous / 40 ° C** | | | **Standby / 27 °C** | | |
|---|---|---|---|---|---|---|---|
| **Class / C° rise** | | H / 125 ° K | | | H / 163° K | | |
| **Series Star( V)** | | 380/220 | 400/231 | 415/240 | 380/220 | 400/231 | 415/240 |
| **Parallel Star (V)** | | 190/110 | 200/115 | 208/120 | 190/110 | 200/115 | 208/120 |
| **Series Delta(V)** | | 220 | 230 | 240 | 220 | 230 | 240 |
| GNP 355 S1 | kVA | 555 | 555 | 566 | 610 | 610 | 623 |
| | kW | 444 | 444 | 453 | 488 | 488 | 498 |
| GNP 355 M | kVA | 600 | 600 | 612 | 660 | 660 | 673 |
| | kW | 480 | 480 | 490 | 528 | 528 | 538 |
| GNP 355 M1 | kVA | 659 | 659 | 672 | 725 | 725 | 739 |
| | kW | 527 | 527 | 538 | 580 | 580 | 591 |
| GNP 355 MX | kVA | 700 | 700 | 717 | 770 | 770 | 789 |
| | kW | 560 | 560 | 574 | 616 | 616 | 868 |
| GNP 355 MXA | kVA | 750 | 750 | 765 | 825 | 825 | 842 |
| | kW | 600 | 600 | 612 | 660 | 660 | 674 |
| GNP 355 L | kVA | 773 | 773 | 788 | 850 | 850 | 867 |
| | kW | 618 | 618 | 630 | 680 | 680 | 694 |
| GNP 355 LX | kVA | 850 | 850 | 867 | 935 | 935 | 954 |
| | kW | 680 | 680 | 694 | 748 | 748 | 763 |

TECHNICAL SPECIFICATIONS

### REACTANCES (%) – TIME CONSTANTS (ms) : CLASS: H / 400 V

| VOLTAGE SERIAL STAR | 400 V | 355 S1 | 355 M | 355 M1 | 355 MX | 355 MXA | 355 L | 355 LX |
|---|---|---|---|---|---|---|---|---|
| DIR. AXIS SYNCHRONOUS | Xd | 2,95 | 2,72 | 2,83 | 2,62 | 2,58 | 2,57 | 2,55 |
| DIR. AXIS TRANSIENT | X'd | 0,16 | 0,14 | 0,15 | 0,14 | 0,14 | 0,14 | 0,14 |
| DIR. AXIS SUBTRANSIENT | X''d | 0,12 | 0,1 | 0,11 | 0,1 | 0,1 | 0,1 | 0,1 |
| QUAD.AXIS REACTANCE | Xq | 2,4 | 2,24 | 2,21 | 2,19 | 2,18 | 2,16 | 2,19 |
| QUAD. AXIS SUBTRANSIENT | X''q | 0,24 | 0,25 | 0,24 | 0,23 | 0,24 | 0,25 | 0,23 |
| LEAKAGE REACTANCE | XL | 0,06 | 0,04 | 0,05 | 0,04 | 0,04 | 0,05 | 0,04 |
| NEGATIVE SEQUENCE | X2 | 0,17 | 0,17 | 0,16 | 0,15 | 0,15 | 0,15 | 0,15 |
| ZERO SEQUENCE | X0 | 0,1 | 0,09 | 0,08 | 0,07 | 0,065 | 0,06 | 0,065 |

### OTHER DATA – CLASS H / 400 V

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| T'd TRANSIENT TIME CONST. | 0,08 s | 0,08 s | 0,08 s | 0,08 s | 0,08 s | 0,08 s | 0,08 s |
| T''d SUB-TRANSTIME CONST. | 0,012 s | 0,012 s | 0,012 s | 0,012 s | 0,012 s | 0,012 s | 0,012 s |
| T'do O.C. FIELD TIME CONST. | 2 s | 2,2 s | 2,5 s | 2,5 s | 2,5 s | 2,5 s | 2,5 s |
| Ta ARMATURE TIME CONST. | 0,017 s | 0,017 s | 0,019 s | 0,019 s | 0,019 s | 0,019 s | 0,019 s |
| SHORT CIRCUIT RATIO | 1/Xd | 1/Xd | 1/Xd | 1/Xd | 1/Xd | 1/Xd | 1/Xd |


GENPOWER GENERATOR


GENPOWER reserves the right to change the values and pictures in this catalogue at any time without notice due to the ongoing developments in generator technology.


## 3 PHASE / 400V / 50 HZ EFFICIENCY CURVES & PERCENT TRANSIENT VOLTAGE DIP & ALTERNATOR WINDINGS


400 V - 50 HZ


STANDARD SPECIFICATIONS

















TECHNICAL SPECIFICATIONS

| ALTERNATOR WINDINGS | | | | | | | |
|---|---|---|---|---|---|---|---|
| 4 Pole | 50 Hz - 1500 R.P.M | | | | | | |
| Phase | 3 | 3 | 3 | 3 | 3 | 1 | 1 |
| Connections |  |  |  |  |  |  |  |
| Number of Leads | 6 | 6 | 12 | 12 | 12 | 12 | 12 |
| Standard Winding | 380 - 400 - 415V | 220 - 240V | 380 - 400 - 415V | 220 - 240V | 190 - 208V | 220 - 240V | 220 - 240V |

High quality 100% copper wires are used in the rotors, stators and excitation wirings of GENPOWER alternators. All metal sheets used in the production are siliceous metals. Therefore, GNP alternators have higher efficiency compared to exemplary products.



GENPOWER reserves the right to change the values and pictures in this catalogue at any time without notice due to the ongoing developments in generator technology.

480 V - 60 HZ

STANDARD SPECIFICATIONS

## ALTERNATOR TECHNICAL DATA – 60HZ

### 4 POLE 1800 RPM 60 HZ

**TYPICAL DATA**

| | | | |
|---|---|---|---|
| **Insulation class** | H | **Control system** | Self Excited |
| **Winding pitch** | 2/3- (N ° 6) | **A.V.R. model** | Standard SX440/MX321+PMG |
| **Wires** | 12 | **Voltage regulation** | ± 1.0 % |
| **Drip proof** | IP 23 | **Sustained short-circuit current** | 300% (3 IN) : 10s |
| **Altitude** | ≤ 1000 m | **Total harmonic (*) TGH / THC** | < 4 % |
| **Overspeed** | 2250 min-1 | **Wave form: NEMA = TIF - (*)** | < 50 |
| **Air flow** | 1.312 sec. | **Wave form: I.E.C. = THF - (*)** | < 2 % |
| **Bearing drive** | - | **Bearing non-drive** | 6314 – 2RZ |

(*)Total harmonic content line to line, at no load or full rated linear and balanced load

### 60 HZ – kVA / kW – Power Factor (Cos Q ) = 0,8

| **Duty Ambient C°** | | **Continuous / 40 ° C** | | | **Standby / 27 °C** | | |
|---|---|---|---|---|---|---|---|
| **Class / C° rise** | | H / 125 ° K | | | H / 163° K | | |
| **Series Star( V)** | | 416/240 | 440/254 | 480/277 | 416/240 | 440/254 | 480/277 |
| **Parallel Star (V)** | | 208/120 | 220/127 | 240/138 | 208/120 | 220/120 | 240/138 |
| **Series Delta(V)** | | 240 | 254 | 277 | 240 | 254 | 277 |
| GNP 355 S1 | kVA | 661 | 696 | 733 | 727 | 766 | 806 |
| | kW | 529 | 557 | 586 | 582 | 613 | 645 |
| GNP 355 M | kVA | 697 | 734 | 773 | 767 | 807 | 850 |
| | kW | 558 | 587 | 618 | 614 | 646 | 680 |
| GNP 355 M1 | kVA | 743 | 782 | 824 | 817 | 860 | 906 |
| | kW | 594 | 626 | 659 | 654 | 688 | 725 |
| GNP 355 MX | kVA | 789 | 831 | 875 | 868 | 914 | 963 |
| | kW | 631 | 665 | 700 | 694 | 731 | 770 |
| GNP 355 MXA | kVA | 846 | 891 | 938 | 931 | 980 | 1032 |
| | kW | 677 | 713 | 750 | 745 | 784 | 826 |
| GNP 355 L | kVA | 865 | 911 | 956 | 951 | 1002 | 1055 |
| | kW | 692 | 729 | 767 | 761 | 802 | 844 |
| GNP 355 LX | kVA | 945 | 995 | 1047 | 1040 | 1095 | 1152 |
| | kW | 756 | 796 | 838 | 832 | 876 | 922 |

TECHNICAL SPECIFICATIONS

### REACTANCES (%) – TIME CONSTANTS (ms) : CLASS: H / 480 V

| VOLTAGE SERIAL STAR | 480 V | 355 S1 | 355 M | 355 M1 | 355 MX | 355 MXA | 355 L | 355 LX |
|---|---|---|---|---|---|---|---|---|
| DIR. AXIS SYNCHRONOUS | Xd | 3,0975 | 2,856 | 2,9715 | 2,751 | 2,709 | 2,6985 | 2,6775 |
| DIR. AXIS TRANSIENT | X'd | 0,168 | 0,147 | 0,1575 | 0,147 | 0,147 | 0,147 | 0,147 |
| DIR. AXIS SUB□RANSIENT | X''d | 0,126 | 0,105 | 0,1155 | 0,105 | 0,105 | 0,105 | 0,105 |
| QUAD.AXIS REACTANCE | Xq | 2,52 | 2,352 | 2,3205 | 2,2995 | 2,289 | 2,268 | 2,2995 |
| QUAD. AXIS SUBTRANSIENT | X''q | 0,252 | 0,2625 | 0,252 | 0,2415 | 0,252 | 0,2625 | 0,2415 |
| LEAKAGE REACTANCE | XL | 0,063 | 0,042 | 0,0525 | 0,042 | 0,042 | 0,0525 | 0,042 |
| NEGATIVE SEQUENCE | X2 | 0,1785 | 0,1785 | 0,168 | 0,1575 | 0,1575 | 0,1575 | 0,1575 |
| ZERO SEQUENCE | X0 | 0,105 | 0,0945 | 0,084 | 0,0735 | 0,06825 | 0,063 | 0,06825 |

### OTHER DATA – CLASS H / 480 V


| | | | | | | | |
|---|---|---|---|---|---|---|---|
| T'd TRANSIENT TIME CONST. | 0,08 s | 0,08 s | 0,08 s | 0,08 s | 0,08 s | 0,08 s | 0,08 s |
| T''d SUB-TRANSTIME CONST. | 0,012 s | 0,012 s | 0,012 s | 0,012 s | 0,012 s | 0,012 s | 0,012 s |
| T'do O.C. FIELD TIME CONST. | 2 s | 2,2 s | 2,5 s | 2,5 s | 2,5 s | 2,5 s | 2,5 s |
| Ta ARMATURE TIME CONST. | 0,017 s | 0,0017 s | 0,019 s | 0,019 s | 0,019 s | 0,019 s | 0,019 s |
| SHORT CIRCUIT RATIO | 1/Xd | 1/Xd | 1/Xd | 1/Xd | 1/Xd | 1/Xd | 1/Xd |


GENPOWER GENERATOR


GENPOWER reserves the right to change the values and pictures in this catalogue at any time without notice due to the ongoing developments in generator technology.


## 3 PHASE / 480V / 60 HZ EFFICIENCY CURVES & PERCENT TRANSIENT VOLTAGE DIP & ALTERNATOR WINDINGS


**480 V - 60 HZ**

















| ALTERNATOR WINDINGS | | | | | | | |
|---|---|---|---|---|---|---|---|
| 4 Pole | 60 Hz - 1800 R.P.M | | | | | | |
| Phase | 3 | 3 | 3 | 3 | 3 | 1 | 1 |
| Connections | | | | | | | |
| Number of Leads | 6 | 6 | 12 | 12 | 12 | 12 | 12 |
| Standard Winding | 380 - 480V | 220 - 277V | 380 - 480V | 220 - 277V | 190 - 240V | 220 - 240V | 220 - 240V |

High quality 100% copper wires are used in the rotors, stators and excitation wirings of GENPOWER alternators. All metal sheets used in the production are siliceous metals. Therefore, GNP alternators have higher efficiency compared to exemplary products.

STANDARD SPECIFICATIONS

TECHNICAL SPECIFICATIONS


GENPOWER GENERATOR


GENPOWER reserves the right to change the values and pictures in this catalogue at any time without notice due to the ongoing developments in generator technology.

DIMENSIONS

## DIMENSIONS

| CONNECTION TYPE | | COUPLING DISC | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| SAE | MODEL | C-G | A | B | D | N | SAE | AN | AR | AS | AT | V |
| 1 | 355 S1-S2 | 555 | 1337 | 1266 | 568 | 493 | 14 | 25,4 | 8 | 13,5 | 438,1 | 466,6 |
| | 355 M-M1 | 575 | 1337 | 1266 | 568 | 493 | FLANGE ADAPTER | | | | | |
| | 355 MX-MXA | 595 | 1337 | 1266 | 568 | 583 | SAE | R | S | T | W | X |
| | 355 L-LX | 620 | 1412 | 1341 | 643 | 583 | 1 | 12 | 12,7 | 530,2 | 496 | 511,1 |




## SPECIAL PRODUCTS / NON - STANDARDIZED

| | |
|---|---|
| Light Tower Alternators | Direct Current Alternators - (DC) |
| Welding Alternators | Medium Voltage Alternators - (MV) |
| High Frequency Alternators | High Voltage Alternators - (HV) |
| Variable Speed Alternators | IP44 and IP54 Class Alternators - (Marine) |

## QUALITY DOCUMENTS & CERTIFICATES

| | | |
|---|---|---|
| Trademark Registration Certificate | Industrial Registry Certificate | TSE – Turkish Standards Institution Certificate |
| Capacity Report (32400 Units /Year) | Certificate of Manufacturing Competence | Certificate of Competency for After Sales Services |
| ISO 9001 - 2015 Certificate | TSE- Service Adequacy Certificate | Made in Turkey Certificate- For Generator/ 1 - 5000 kVA |
| ISO 14001 - 2015 Certificate | TS EN 60034 - 1 Certificate | |
| OHSAS 18001 - 2007 Certificate | | |



GENPOWER reserves the right to change the values and pictures in this catalogue at any time without notice due to the ongoing developments in generator technology.

# GENPOWER®
GENERATOR

**Your Power is the Core Our Business...**






SCAN ME

www.genpower.gen.tr

ISO 9001:2008
OHSAS 18001:2007
ISO 14001:2004

Central District, Kağıthane Street
Y Office No:5 Interior No:37, 34406
Kağıthane-ISTANBUL / TURKEY
+90 (536) 351 34 00
+90 (536) 351 65 00
+90 (212) 294 94 22
+90 (212) 294 94 33
info@genpower.gen.tr